

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Product name : ACTIVATOR-INTERMIX 4:1 PRIMER B
Product code : FEB0181

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Endura Manufacturing Company Ltd.
12425 149 Street NW
Edmonton, T5L 2J6 - Canada
T 1-780-451-4242 - F 1-780-452-5079
info@endura.ca - www.endurapaint.com

1.4. Emergency telephone number

Emergency number : In the event of an emergency involving dangerous goods:
in Canada call CHEMTREC at 1-800-424-9300 24 hours / 7 days (Account Name for Canada Endura Manufacturing Co. Ltd.)
in the US call CHEMTREC at 1-800-424-9300 24 hours / 7 days (Account Name for US is Polyglass Coatings)

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Flammable liquids Category 3	H226	Flammable liquid and vapor
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction

Full text of H statements : see section 16

2.2. Label elements**GHS US labeling**

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H332 - Harmful if inhaled

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center or doctor
P312 - Call a poison center/doctor/physician if you feel unwell
P321 - Specific treatment (see 4.1. First aid procedures on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	wt%	GHS US classification
xylene, mixture of isomers	(CAS-No.) 1330-20-7	27.871	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
nonylphenol, isomer mixture	(CAS-No.) 25154-52-3	10 – 20	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314
benzyl alcohol	(CAS-No.) 100-51-6	< 12.681	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
1-butanol	(CAS-No.) 71-36-3	10 – 20	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
2-butoxyethylacetate	(CAS-No.) 112-07-2	5 – 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2	< 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319
triethylenetetramine	(CAS-No.) 112-24-3	< 1.087	Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
tetraethylenepentamine	(CAS-No.) 112-57-2	< 0.906	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1A, H314 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off all contaminated clothing immediately. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a physician immediately.

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor.
Reactivity	: Flammable liquid and vapor.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene, mixture of isomers (1330-20-7)		
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

xylene, mixture of isomers (1330-20-7)		
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (STEL) (mg/m ³)	655 mg/m ³

2-butoxyethylacetate (112-07-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Hemolysis

1-butanol (71-36-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	300 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear respiratory protection.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Pleasant odour Aromatic odour Fruity odour Mild odour Ammonia odour Phenol odour Amine-like odour Irritating/pungent odour Alcohol odour Sweet odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 100 °C 212 °F
Flash point	: 26 °C 78.8 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: 0.9 – 11.25 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.9302 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition temperature	: 449 °C 840 °F
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

VOC content (Regulatory - Less water and exempt solvents)	: 534.061 g/l 4.457 lb/gal
VOC content (Material - Actual)	: 534.061 g/l 4.457 lb/gal
Percent Solids (Weight)	: 42.58 %
Percent Solids (Volume)	: 40.195 %
Percent Volatile (Weight)	: 57.414 %
Percent Volatile (Volume)	: 59.805 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	: Dermal; Inhalation; Skin and eye contact
Acute toxicity	: Not classified

ACTIVATOR-INTERMIX 4:1 PRIMER B	
ATE US (dust, mist)	3.207 mg/l/4h
xylene, mixture of isomers (1330-20-7)	
LD50 oral rat	3523 – 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4200 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (vapors)	29 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
2-butoxyethylacetate (112-07-2)	
LD50 oral rat	1880 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	1500 mg/kg (24 h, Rabbit, Experimental value, Dermal, 14 day(s))
ATE US (oral)	1880 mg/kg body weight
ATE US (dermal)	1500 mg/kg body weight

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-butoxyethylacetate (112-07-2)	
ATE US (dust, mist)	1.5 mg/l/4h
nonylphenol, isomer mixture (25154-52-3)	
LD50 oral rat	1000 – 2000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Literature study, Dermal)
ATE US (oral)	1000 mg/kg body weight
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LD50 oral rat	2169 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
ATE US (oral)	2169 mg/kg body weight
1-butanol (71-36-3)	
LD50 oral rat	2292 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	3430 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
ATE US (oral)	2292 mg/kg body weight
ATE US (dermal)	3430 mg/kg body weight
benzyl alcohol (100-51-6)	
LD50 oral rat	1620 mg/kg bw/day (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg (EPA OTS 798.1100, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	> 4.18 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
ATE US (oral)	1620 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
tetraethylenepentamine (112-57-2)	
LD50 oral rat	3990 mg/kg (Rat; Literature study; 3250 mg/kg bodyweight; Rat; Literature study)
LD50 dermal rabbit	660 mg/kg (Rabbit; Literature study; 660-1260 mg/kg bodyweight; Rabbit; Literature study)
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	660 mg/kg body weight
triethylenetetramine (112-24-3)	
LD50 oral rat	2500 mg/kg (Rat; Literature; 1716 mg/kg bodyweight; Rat; Literature)
LD50 dermal rabbit	805 mg/kg (Rabbit; Literature; 1465 mg/kg bodyweight; Rabbit; Literature)
ATE US (oral)	2500 mg/kg body weight
ATE US (dermal)	805 mg/kg body weight
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Assumed to cause serious eye damage
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
xylene, mixture of isomers (1330-20-7)	
IARC group	3 - Not Classifiable

Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

2-butoxyethylacetate (112-07-2)	
LC50 fish 1	20 – 40 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	37 mg/l (DIN 38412-11, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	1570 mg/l (ISO 8692, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

nonylphenol, isomer mixture (25154-52-3)	
LC50 fish 1	0.56 – 0.92 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Literature)
EC50 Daphnia 1	0.14 mg/l (48 h, Daphnia magna, Experimental value, GLP)

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 fish 1	175 mg/l (APHA, 96 h, Cyprinus carpio, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)

1-butanol (71-36-3)	
LC50 fish 1	1376 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	1328 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	225 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

benzyl alcohol (100-51-6)	
LC50 fish 1	460 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	230 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	770 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

tetraethylenepentamine (112-57-2)	
EC50 Daphnia 1	24.1 mg/l (EC50; EU Method C.2; 48 h; Daphnia magna; Static system)
LC50 fish 2	420 mg/l (LC50; EU Method C.1; 96 h; Poecilia reticulata; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 1	0.5 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum)
Threshold limit algae 2	6.8 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum)

triethylenetetramine (112-24-3)	
EC50 Daphnia 1	311 mg/l (EC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna)
LC50 fish 2	495 mg/l (LC50; 96 h; Pimephales promelas)
Threshold limit algae 1	≥ 100 mg/l (ErC50; DIN 38412-9; 72 h; Scenedesmus subspicatus)

12.2. Persistence and degradability

xylene, mixture of isomers (1330-20-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test) data on mobility of the substance available. Photolysis in the air.

2-butoxyethylacetate (112-07-2)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.1 g O ₂ /g substance

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

nonylphenol, isomer mixture (25154-52-3)	
Persistence and degradability	Non degradable in the soil. Not readily biodegradable in water.
ThOD	2.97 g O ₂ /g substance
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Persistence and degradability	Not readily biodegradable in water.
1-butanol (71-36-3)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.1 – 1.92 g O ₂ /g substance
Chemical oxygen demand (COD)	2.46 g O ₂ /g substance
ThOD	2.59 g O ₂ /g substance
BOD (% of ThOD)	0.33 – 0.79
benzyl alcohol (100-51-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.6 g O ₂ /g substance
Chemical oxygen demand (COD)	2.4 g O ₂ /g substance
ThOD	2.5 g O ₂ /g substance
tetraethylenepentamine (112-57-2)	
Persistence and degradability	Not readily biodegradable in water. Low potential for mobility in soil. Adsorbs into the soil.
triethylenetetramine (112-24-3)	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available. Photodegradation in the air.

12.3. Bioaccumulative potential

xylene, mixture of isomers (1330-20-7)	
BCF fish 2	7 – 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Conclusion by analogy; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
2-butoxyethylacetate (112-07-2)	
Partition coefficient n-octanol/water (Log Pow)	1.51 (Experimental value, BASF test, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
nonylphenol, isomer mixture (25154-52-3)	
BCF fish 1	271 (20 day(s), Pimephales promelas, Fresh water, Experimental value, GLP)
Partition coefficient n-octanol/water (Log Pow)	3.28 (Test data, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Pow)	-0.66 (Experimental value, EPA OPPTS 830.7550: Partition Coefficient (n-octanol/water), Shake Flask Method, 21.5 °C)
Bioaccumulative potential	Not bioaccumulative.
1-butanol (71-36-3)	
BCF other aquatic organisms 1	3.162 l/kg (BCFBAF v3.01, Calculated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
benzyl alcohol (100-51-6)	
Partition coefficient n-octanol/water (Log Pow)	1 – 1.1 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
tetraethylenepentamine (112-57-2)	
BCF other aquatic organisms 1	4.2 (BCF)
Partition coefficient n-octanol/water (Log Pow)	-3.16 (Calculated; EPIWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

triethylenetetramine (112-24-3)	
Partition coefficient n-octanol/water (Log Pow)	-1.86 – -1.41 (Calculated)
Bioaccumulative potential	Bioaccumulation: not applicable.

12.4. Mobility in soil

xylene, mixture of isomers (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

2-butoxyethylacetate (112-07-2)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Koc)	1.179 – 1.637 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

nonylphenol, isomer mixture (25154-52-3)	
Ecology - soil	Adsorbs into the soil.

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Koc)	1.32 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

1-butanol (71-36-3)	
Surface tension	69.9 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Partition coefficient n-octanol/water (Log Koc)	0.54 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil. May be harmful to plant growth, blooming and fruit formation.

benzyl alcohol (100-51-6)	
Surface tension	39 mN/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.122 – 1.332 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint related material (including paint thinning, drying, removing, or reducing compound), 3, III

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint related material
including paint thinning, drying, removing, or reducing compound

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
- Other information : No supplementary information available.

Transportation of Dangerous Goods

- Transport document description : UN1263 PAINT RELATED MATERIAL (PAINT RELATED MATERIAL), 3, III
- UN-No. (TDG) : UN1263
- Proper Shipping Name (Transportation of Dangerous Goods) : PAINT RELATED MATERIAL
- TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
- Packing group : III - Minor Danger
- TDG Special Provisions : 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass),83 - Repealed SOR/2014-152
- Explosive Limit and Limited Quantity Index : 5
- Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 60

Transport by sea

- UN-No. (IMDG) : 1263
- Proper Shipping Name (IMDG) : PAINT RELATED MATERIAL
- Class (IMDG) : 3 - Flammable liquids
- Packing group (IMDG) : III - substances presenting low danger

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

xylene, mixture of isomers	CAS-No. 1330-20-7	27.871%
1-butanol	CAS-No. 71-36-3	10 – 20%

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

xylene, mixture of isomers (1330-20-7)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ	100 lb

1-butanol (71-36-3)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ	5000 lb

15.2. International regulations

CANADA

ACTIVATOR-INTERMIX 4:1 PRIMER B
Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

xylene, mixture of isomers (1330-20-7)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

2-butoxyethylacetate (112-07-2)
U.S. - New Jersey - Right to Know Hazardous Substance List

1-butanol (71-36-3)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

tetraethylenepentamine (112-57-2)
U.S. - New Jersey - Right to Know Hazardous Substance List

triethylenetetramine (112-24-3)
U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 06/03/2021

ACTIVATOR-INTERMIX 4:1 PRIMER B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS US Endura

The information contained here has been compiled from sources considered by Endura Manufacturing Co. Ltd to be dependable and is accurate to the best of the Company's knowledge. However, neither Endura Manufacturing Co. Ltd or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.