

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Product name : ULTRAFLEX CLEAR A
Product code : FUA0204
Formula : FUA0208TL

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Endura Manufacturing Company Ltd.
12425 149 Street NW
Edmonton, T5L 2J6 - Canada
T 1-780-451-4242 - F 1-780-452-5079
info@endura.ca - www.endurapaint.com

1.4. Emergency telephone number

Emergency number : In the event of an emergency involving dangerous goods:
in Canada call CHEMTREC at 1-800-424-9300 24 hours / 7 days (Account Name for Canada
Endura Manufacturing Co. Ltd.)
in the US call CHEMTREC at 1-800-424-9300 24 hours / 7 days (Account Name for US is
Polyglass Coatings)


SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled
Specific target organ toxicity (single exposure) Category 3	H336	May cause drowsiness or dizziness

Full text of H statements : see section 16

2.2. Label elements**GHS US labeling**

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P312 - Call a poison center/doctor/physician if you feel unwell
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2) to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.

ULTRAFLEX CLEAR A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up.
P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	wt%	GHS US classification
n-butyl acetate	(CAS-No.) 123-86-4	20 – 30	Flam. Liq. 3, H226 Acute Tox. 2 (Inhalation:vapour), H330 STOT SE 3, H336
ethyl acetate	(CAS-No.) 141-78-6	< 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
heptan-2-one	(CAS-No.) 110-43-0	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:vapour), H332
xylene, mixture of isomers	(CAS-No.) 1330-20-7	1.736	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off all contaminated clothing immediately.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : May cause moderate irritation.
Symptoms/effects after eye contact : Irritation to eyes.
Symptoms/effects after ingestion : Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.
Reactivity : Highly flammable liquid and vapor.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

ULTRAFLEX CLEAR A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene, mixture of isomers (1330-20-7)		
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (STEL) (mg/m ³)	655 mg/m ³

n-butyl acetate (123-86-4)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	710 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	150 ppm

ethyl acetate (141-78-6)		
ACGIH	ACGIH TWA (ppm)	400 ppm
ACGIH	Remark (ACGIH)	URT & eye irr
OSHA	OSHA PEL (TWA) (mg/m ³)	1400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	400 ppm

heptan-2-one (110-43-0)		
ACGIH	ACGIH TWA (ppm)	50 ppm

ULTRAFLEX CLEAR A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

heptan-2-one (110-43-0)		
ACGIH	Remark (ACGIH)	Eye & skin irr
OSHA	OSHA PEL (TWA) (mg/m ³)	465 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear respiratory protection.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Pleasant odour Aromatic odour Fruity odour Strong odour Characteristic odour Petroleum-like odour Mild odour Ether-like odour Sweet odour Irritating/pungent odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 77 °C 170.6 °F
Flash point	: -4 °C 24.8 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: 1 – 13.7 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.0129 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

VOC content (Regulatory - Less water and exempt solvents)	: 414.01 g/l 3.455 lb/gal
VOC content (Material - Actual)	: 414.01 g/l 3.455 lb/gal
Percent Solids (Weight)	: 59.13 % (wt%)
Percent Solids (Volume)	: 52.75 %
Percent Volatile (Weight)	: 40.87 %

ULTRAFLEX CLEAR A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Percent Volatile (Volume) : 47.25 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Dermal; Inhalation; Skin and eye contact

Acute toxicity : Not classified

ULTRAFLEX CLEAR A	
ATE US (dust, mist)	2.438 mg/l/4h
xylene, mixture of isomers (1330-20-7)	
LD50 oral rat	3523 – 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4200 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (vapors)	29 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
n-butyl acetate (123-86-4)	
LD50 oral rat	10760 – 12789 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 14112 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	0.74 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Inhalation (mixture of vapour and aerosol), 14 day(s))
ATE US (oral)	10760 mg/kg body weight
ATE US (vapors)	0.74 mg/l/4h
ATE US (dust, mist)	0.74 mg/l/4h
ethyl acetate (141-78-6)	
LD50 oral rat	10200 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 20000 mg/kg body weight (24 hour cuff method, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE US (oral)	10200 mg/kg body weight
heptan-2-one (110-43-0)	
LD50 oral rat	1600 mg/kg body weight (Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	> 16.7 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

ULTRAFLEX CLEAR A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

heptan-2-one (110-43-0)	
ATE US (oral)	1600 mg/kg body weight
ATE US (vapors)	11 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

xylene, mixture of isomers (1330-20-7)	
IARC group	3 - Not Classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause moderate irritation.
Symptoms/effects after eye contact	: Irritation to eyes.
Symptoms/effects after ingestion	: Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
-------------------	---

n-butyl acetate (123-86-4)	
LC50 fish 1	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	44 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia sp., Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)

ethyl acetate (141-78-6)	
LC50 fish 1	230 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

heptan-2-one (110-43-0)	
LC50 fish 1	131 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	> 90.1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

xylene, mixture of isomers (1330-20-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air.

n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O ₂ /g substance
BOD (% of ThOD)	0.46

ethyl acetate (141-78-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.293 g O ₂ /g substance

ULTRAFLEX CLEAR A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethyl acetate (141-78-6)	
Chemical oxygen demand (COD)	1.69 g O ₂ /g substance
ThOD	1.82 g O ₂ /g substance

heptan-2-one (110-43-0)	
Persistence and degradability	Readily biodegradable in water.
BOD (% of ThOD)	0.44

12.3. Bioaccumulative potential

xylene, mixture of isomers (1330-20-7)	
BCF fish 2	7 – 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Conclusion by analogy; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

ethyl acetate (141-78-6)	
BCF fish 1	30 (3 day(s), Leuciscus idus, Static renewal, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	0.68 (Experimental value, EPA OPPTS 830.7560, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

heptan-2-one (110-43-0)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

xylene, mixture of isomers (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

n-butyl acetate (123-86-4)	
Surface tension	61.3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)
Partition coefficient n-octanol/water (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

ethyl acetate (141-78-6)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.

heptan-2-one (110-43-0)	
Surface tension	0.0591 N/m (21.6 °C, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Koc)	1.45 (log Koc, EU Method C.19, Experimental value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, II

UN-No.(DOT) : UN1263

ULTRAFLEX CLEAR A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (DOT) : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport document description : UN1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, II

UN-No. (TDG) : UN1263

Proper Shipping Name (Transportation of Dangerous Goods) : PAINT

TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids

Packing group : II - Medium Danger

ULTRAFLEX CLEAR A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	: 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass), 142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a) "PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b) "PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c) "PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d) "PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material. SOR/2014-306
Explosive Limit and Limited Quantity Index	: 5 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L

Transport by sea

Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

xylene, mixture of isomers	CAS-No. 1330-20-7	1.736%
xylene, mixture of isomers (1330-20-7)		
Listed on SARA Section 313 (Specific toxic chemical listings)		
CERCLA RQ	100 lb	
n-butyl acetate (123-86-4)		
Not listed on SARA Section 313 (Specific toxic chemical listings)		
CERCLA RQ	5000 lb	
ethyl acetate (141-78-6)		
Not listed on SARA Section 313 (Specific toxic chemical listings)		
CERCLA RQ	5000 lb	

15.2. International regulations

CANADA

ULTRAFLEX CLEAR A
Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

ULTRAFLEX CLEAR A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

xylene, mixture of isomers (1330-20-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

n-butyl acetate (123-86-4)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

ethyl acetate (141-78-6)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

heptan-2-one (110-43-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 06/10/2021

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H330	Fatal if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness

SDS US Endura

The information contained here has been compiled from sources considered by Endura Manufacturing Co. Ltd to be dependable and is accurate to the best of the Company's knowledge. However, neither Endura Manufacturing Co. Ltd or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.