ACTIVATOR-EX-2C ELECTROSTATIC B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 11/06/2015 Revision date: 05/17/2024 Supersedes: 06/16/2021 Version: 1.3

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : ACTIVATOR-EX-2C ELECTROSTATIC B

Product code : FUB0103

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Endura Manufacturing Company Ltd.
12425 - 149 Street NW
Edmonton, AB, T5L 2J6 - Canada
T 1-780-451-4242 - F 1-780-452-5079
info@endura.ca - www.endurapaint.com

1.4. Emergency telephone number

Emergency number : In the event of an emergency involving dangerous goods:
in Canada call CHEMTREC at 1-800-424-9300 24 hours / 7 days (Account Name for Canada Endura Manufacturing Co. Ltd.)
in the US call CHEMTREC at 1-800-424-9300 24 hours / 7 days (Account Name for US is Polyglass Coatings)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled
Respiratory sensitization, Category 1	H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :

GHS02 GHS07 GHS08

Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H317 - May cause an allergic skin reaction
H332 - Harmful if inhaled
H334 - May cause an allergy or asthma symptoms or breathing difficulties if inhaled
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P284 - [In case of inadequate ventilation] wear respiratory protection.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P304+P341 - If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P312 - Call a poison center/doctor/physician if you feel unwell
P321 - Specific treatment (see 4.1. First aid procedures on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P342+P311 - If experiencing respiratory symptoms: Call a poison center or doctor.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2) to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

2.4. Unknown acute toxicity (GHS US)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	wt%	GHS US classification
n-butyl acetate	(CAS-No.) 123-86-4	20 – 30	Flam. Liq. 3, H226 Acute Tox. 2 (Inhalation:vapour), H330 STOT SE 3, H336
ethyl acetate	(CAS-No.) 141-78-6	< 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
heptan-2-one	(CAS-No.) 110-43-0	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:vapour), H332
1,6-diisocyanatohexane	(CAS-No.) 822-06-0	0.397	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off all contaminated clothing immediately. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. May cause an allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after skin contact : None under normal conditions. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Irritation to eyes.

Symptoms/effects after ingestion : Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard. Highly flammable liquid and vapor.

Explosion hazard : No direct explosion hazard.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport. Highly flammable liquid and vapor.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat. Ground/bond container and receiving equipment.

Storage conditions : Keep cool. Protect from sunlight. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

n-butyl acetate (123-86-4)		
ACGIH	ACGIH OEL TWA	50 ppm
ACGIH	ACGIH OEL STEL	150 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL TWA	710 mg/m³
OSHA	OSHA PEL TWA	150 ppm

1,6-diisocyanatohexane (822-06-0)		
ACGIH	ACGIH OEL TWA	0.005 ppm
ACGIH	Remark (ACGIH)	URT irr; resp sens

ethyl acetate (141-78-6)		
ACGIH	ACGIH OEL TWA	400 ppm
ACGIH	Remark (ACGIH)	URT & eye irr
OSHA	OSHA PEL TWA	1400 mg/m³
OSHA	OSHA PEL TWA	400 ppm

heptan-2-one (110-43-0)		
ACGIH	ACGIH OEL TWA	50 ppm
ACGIH	Remark (ACGIH)	Eye & skin irr
OSHA	OSHA PEL TWA	465 mg/m³
OSHA	OSHA PEL TWA	100 ppm

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Wear recommended personal protective equipment.

Hand protection : Protective gloves.

Eye protection : Safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. [In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Mixture contains one or more component(s) which have the following colour(s):
Colourless Colourless to light yellow

Odor : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.
Mixture contains one or more component(s) which have the following odour:
Fruity odour Pleasant odour Mild odour Irritating/pungent odour

Odor threshold : No data available

pH	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	77 – 78 °C 171 – 172 °F
Flash point	:	-4 °C 25 °F
Relative evaporation rate (butyl acetate=1)	:	No data available
Flammability	:	No data available
Explosion limits	:	2.1 – 11.5 vol %
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Relative vapor density at 20°C	:	No data available
Density	:	0.977 g/cm³
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	426 – 485 °C 799 – 905 °F
Decomposition temperature	:	No data available
Viscosity	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available

9.2. Other information

VOC content (Regulatory - Less water and exempt solvents)	:	589.59 g/l
	:	4.92 lb/gal
VOC content (Material - Actual)	:	589.59 g/l
	:	4.92 lb/gal
Percent Solids (Weight)	:	39.67 %
Percent Solids (Volume)	:	34.222 %
Percent Volatile (Weight)	:	60.33 %
Percent Volatile (Volume)	:	65.778 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	:	Dermal; Inhalation; Skin and eye contact

Acute toxicity : Not classified

ACTIVATOR-EX-2C ELECTROSTATIC B	
ATE US (dust, mist)	2.518 mg/l/4h

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 – 12789 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 14112 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	0.74 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Inhalation (mixture of vapour and aerosol), 14 day(s))
ATE US (oral)	10760 mg/kg body weight
ATE US (vapors)	0.74 mg/l/4h
ATE US (dust, mist)	0.74 mg/l/4h

1,6-diisocyanatohexane (822-06-0)	
LD50 oral rat	746 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 7000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	0.124 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 28 day(s))
ATE US (oral)	746 mg/kg body weight
ATE US (vapors)	0.124 mg/l/4h
ATE US (dust, mist)	0.124 mg/l/4h

ethyl acetate (141-78-6)	
LD50 oral rat	10200 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 20000 mg/kg body weight (24 hour cuff method, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE US (oral)	10200 mg/kg body weight

heptan-2-one (110-43-0)	
LD50 oral rat	1600 mg/kg body weight (Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 16.7 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1600 mg/kg body weight
ATE US (vapors)	11 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. May cause an allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after skin contact : None under normal conditions. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Irritation to eyes.

Symptoms/effects after ingestion : Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	44 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia sp., Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)

ethyl acetate (141-78-6)	
LC50 - Fish [1]	230 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

heptan-2-one (110-43-0)	
LC50 - Fish [1]	131 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 90.1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O_2/g substance
BOD (% of ThOD)	0.46

1,6-diisocyanatohexane (822-06-0)	
Persistence and degradability	Not readily biodegradable in water.

ethyl acetate (141-78-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.293 g O_2/g substance
Chemical oxygen demand (COD)	1.69 g O_2/g substance
ThOD	1.82 g O_2/g substance

heptan-2-one (110-43-0)	
Persistence and degradability	Readily biodegradable in water.
BOD (% of ThOD)	0.44

12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

1,6-diisocyanatohexane (822-06-0)	
BCF - Fish [1]	59.6 (BCFWIN, Pisces, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

ethyl acetate (141-78-6)	
BCF - Fish [1]	30 (3 day(s), Leuciscus idus, Static renewal, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	0.68 (Experimental value, EPA OPPTS 830.7560, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

heptan-2-one (110-43-0)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

n-butyl acetate (123-86-4)	
Surface tension	61.3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

1,6-diisocyanatohexane (822-06-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.78 – 3.68 (log Koc, Calculated value)
Ecology - soil	Low potential for mobility in soil.

ethyl acetate (141-78-6)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.

heptan-2-one (110-43-0)	
Surface tension	0.0591 N/m (21.6 °C, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.45 (log Koc, EU Method C.19, Experimental value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers. Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN1263 Paint related material, 3, II

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint related material

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid

Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102)	:	149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons). 367 - For the purposes of documentation and package marking: a. The proper shipping name “Paint related material” may be used for consignments of packages containing “Paint” and “Paint related material” in the same package; b. The proper shipping name “Paint related material, corrosive, flammable” may be used for consignments of packages containing “Paint, corrosive, flammable” and “Paint related material, corrosive, flammable” in the same package; c. The proper shipping name “Paint related material, flammable, corrosive” may be used for consignments of packages containing “Paint, flammable, corrosive” and “Paint related material, flammable, corrosive” in the same package; and d. The proper shipping name “Printing ink related material” may be used for consignments of packages containing “Printing ink” and “Printing ink related material” in the same package. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. B131 - When transported by highway, rail, or cargo vessel, waste Paint and Paint related material (UN1263; PG II and PG III), when in plastic or metal inner packagings of not more than 26.5 L (7 gallons), are excepted from the marking requirements in §172.301(a) and (c) and the labeling requirements in §172.400(a), when further packed in the following specification and non-specification bulk outer packagings and under the following conditions: a. Primary receptacles must conform to the general packaging requirements of subpart B of part 173 of this subchapter and may not leak. If they do leak, they must be overpacked in packagings conforming to the specification requirements of part 178 of this subchapter or in salvage packagings conforming to the requirements in §173.12 of this subchapter. b. Primary receptacles must be further packed in non-specification bulk outer packagings such as cubic yard boxes, plastic rigid-wall bulk containers, dump trailers, and roll-off containers. Bulk outer packagings must be liquid tight through design or by the use of lining materials. c. Primary receptacles may also be further packed in specification bulk outer packagings. Authorized specification bulk outer packagings are UN11G fiberboard intermediate bulk containers (IBC) and UN13H4 woven plastic, coated and with liner flexible intermediate bulk containers (FIBCs) meeting the Packing Group II performance level and lined with a plastic liner of at least 6 mil thickness. d. All inner packagings placed inside bulk outer packagings must be blocked and braced to prevent movement during transportation that could cause the container to open or fall over. Specification IBCs and FIBCs are to be secured to a pallet. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F). TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	60 L
DOT Vessel Stowage Location	:	B - (i) The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) ‘‘On deck only’’ on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Emergency Response Guide (ERG) Number	:	128
Other information	:	No supplementary information available.

Transportation of Dangerous Goods

Transport document description (TDG)	:	UN1263 PAINT RELATED MATERIAL, 3, II

UN-No. (TDG)	:	UN1263
Proper Shipping Name (TDG)	:	PAINT RELATED MATERIAL
TDG Primary Hazard Classes	:	3 - Class 3 - Flammable Liquids
Packing group (TDG)	:	II - Medium Danger
TDG Special Provisions	:	59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20% nitrocellulose if the nitrocellulose contains not more than 12.6% nitrogen (by dry mass),142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a) “PAINT RELATED MATERIAL” may be used for a means of containment containing both paint and paint related material; (b) “PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE” may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c) “PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE” may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d) “PRINTING INK RELATED MATERIAL” may be used for a means of containment containing both printing ink and printing ink related material.
Explosive Limit and Limited Quantity Index	:	5 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	:	5 L

Transport by sea

UN-No. (IMDG)	:	1263
Proper Shipping Name (IMDG)	:	PAINT RELATED MATERIAL
Class (IMDG)	:	3 - Flammable liquids
Packing group (IMDG)	:	II - substances presenting medium danger

Air transport

UN-No. (IATA)	:	1263
Proper Shipping Name (IATA)	:	Paint related material
Class (IATA)	:	3 - Flammable Liquids
Packing group (IATA)	:	II - Medium danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

n-butyl acetate	CAS-No. 123-86-4	20 – 30%
1,6-diisocyanatohexane	CAS-No. 822-06-0	0.397%
ethyl acetate	CAS-No. 141-78-6	< 5%
heptan-2-one	CAS-No. 110-43-0	< 5%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

1,6-diisocyanatohexane	CAS-No. 822-06-0	0.397%

n-butyl acetate (123-86-4)	
Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	5000 lb

1,6-diisocyanatohexane (822-06-0)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ	100 lb

ethyl acetate (141-78-6)	
Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	5000 lb

15.2. International regulations

CANADA

ACTIVATOR-EX-2C ELECTROSTATIC B
Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations
No additional information available

National regulations
No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

n-butyl acetate (123-86-4)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

1,6-diisocyanatohexane (822-06-0)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

ethyl acetate (141-78-6)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

heptan-2-one (110-43-0)
U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 05/17/2024

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H330	Fatal if inhaled
H332	Harmful if inhaled
H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

SDS US Endura