

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/02/2021

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC
 Product code : FUSION 90 SOLID COLOR (LF) LEAD FREE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : This product information is generic in nature, and all information including (Solids, Volatiles, VOC's etc.) does not necessarily represent the color being sprayed. If color specific SDS information is required please contact Endura.

1.3. Details of the supplier of the safety data sheet

Endura Manufacturing Co. Ltd.
 12425 149th Street NW
 Edmonton, T5L 2J6 - Canada
 T 1-780-451-4242 - F 1-780-452-5079
www.enduraaviation.com

1.4. Emergency telephone number

Emergency number : In the event of an emergency involving dangerous goods:
 in Canada call CHEMTREC at 1-800-424-9300 24 hours / 7 days (Account Name for Canada Endura Manufacturing Co. Ltd.)
 in the US call CHEMTREC at 1-800-424-9300 24 hours / 7 days (Account Name for US is Polyglass Coatings)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Germ cell mutagenicity Category 1B	H340	May cause genetic defects
Carcinogenicity Category 1A	H350	May cause cancer

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor
 H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation
 H340 - May cause genetic defects
 H350 - May cause cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/Bond container and receiving equipment
 P241 - Use explosion-proof electrical/ventilating/lighting equipment
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P264 - Wash thoroughly after handling
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention.
P321 - Specific treatment (see 4.1. First aid procedures on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	wt%	GHS US classification
titanium(IV) oxide		0 – 60	Carc. 2, H351
2-propoxyethanol	(CAS-No.) 2807-30-9	1 – 44.74	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2, H319
1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	(CAS-No.) 17557-23-2	0 – 10	Skin Irrit. 2, H315 Skin Sens. 1, H317
xylene, mixture of isomers	(CAS-No.) 1330-20-7	0.002 – 1.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
Stoddard solvent	(CAS-No.) 8052-41-3	0 – 0.612	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
ethylbenzene	(CAS-No.) 100-41-4	0.001 – 0.5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
quartz, conc respirable crystalline silica≥10%	(CAS-No.) 14808-60-7	0 – 0.1	Carc. 1A, H350

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off all contaminated clothing immediately. If skin irritation or rash occurs: Get medical advice/attention.

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : May cause moderate irritation. Irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Irritation to eyes.
- Symptoms/effects after ingestion : Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapor.
- Explosion hazard : May form flammable/explosive vapor-air mixture.
- Reactivity : Flammable liquid and vapor.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray. For further information refer to section 8 Exposure controls/personal protection".
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 8 : Exposure-controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical/ventilating/lighting equipment. Ground/bond container and receiving equipment.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Incompatible products : Strong bases. strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

titanium(IV) oxide		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
ACGIH	Remark (ACGIH)	LRT irr; A3
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³

xylene, mixture of isomers (1330-20-7)		
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (STEL) (mg/m ³)	655 mg/m ³

ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm (Ethyl benzene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

quartz, conc respirable crystalline silica≥10% (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (Respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	0.1 mg/m ³
OSHA	Remark (OSHA)	(3) See Table Z-3.

Stoddard solvent (8052-41-3)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & kidney dam;
OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses. Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.
Environmental exposure controls	: Avoid release to the environment.
Other information	: When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 151 °C 303.8 °F
Flash point	: 51.66 °C 125 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: 1.3 – 15.8 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1 – 1.8 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Sparks. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Dermal; Inhalation; Skin and eye contact

Acute toxicity : Not classified

titanium(IV) oxide	
LD50 oral rat	> 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LC50 inhalation rat (mg/l)	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))

2-propoxyethanol (2807-30-9)	
LD50 oral rat	3089 – 6178 mg/kg body weight (Rat, Male, Experimental value, Oral)
LD50 dermal rabbit	1337 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	> 9.061 mg/l (6 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE US (oral)	3089 mg/kg body weight
ATE US (dermal)	1337 mg/kg body weight

xylene, mixture of isomers (1330-20-7)	
LD50 oral rat	3523 – 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4200 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (vapors)	29 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15415 mg/kg body weight
ATE US (gases)	4000 ppmV/4h
ATE US (vapors)	17.8 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

quartz, conc respirable crystalline silica≥10% (14808-60-7)	
LD50 oral rat	> 5000 mg/kg

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane (17557-23-2)	
LD50 oral rat	4500 mg/kg (Rat, Literature study, Oral)
LD50 dermal rat	> 2100 mg/kg body weight (Rat, Literature study, Dermal)
ATE US (oral)	4500 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : May cause cancer.

xylene, mixture of isomers (1330-20-7)	
IARC group	3 - Not Classifiable

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylbenzene (100-41-4)	
IARC group	2B - Possibly Carcinogenic to Humans

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met. Harmful if inhaled.

Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : May cause moderate irritation. Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Irritation to eyes.

Symptoms/effects after ingestion : Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

titanium(IV) oxide	
LC50 fish 1	> 100 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

2-propoxyethanol (2807-30-9)	
LC50 fish 1	> 5000 mg/l (EPA 600/4-85/013: Method for measuring the acute toxicity of effluents to freshwater and marine organisms, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Lethal)
ErC50 (algae)	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

ethylbenzene (100-41-4)	
LC50 fish 2	4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value)

quartz, conc respirable crystalline silica\geq10% (14808-60-7)	
LC50 fish 1	> 500 mg/l
EC50 Daphnia 1	> 300 mg/l

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane (17557-23-2)	
LC50 fish 1	> 100 mg/l (96 h, Pisces, QSAR)
EC50 Daphnia 1	39 – 57 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC	
Persistence and degradability	Not established.

titanium(IV) oxide	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

2-propoxyethanol (2807-30-9)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

xylene, mixture of isomers (1330-20-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air.

ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	45.4 (20 days)

quartz, conc respirable crystalline silica≥10% (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane (17557-23-2)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC	
Bioaccumulative potential	Not established.

titanium(IV) oxide	
Bioaccumulative potential	Not bioaccumulative.

2-propoxyethanol (2807-30-9)	
BCF other aquatic organisms 1	0.6 – 0.7 (Estimated value)
Partition coefficient n-octanol/water (Log Pow)	0.673 (Experimental value, EU Method A.8: Partition Coefficient, 40 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

xylene, mixture of isomers (1330-20-7)	
BCF fish 2	7 – 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Conclusion by analogy; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

ethylbenzene (100-41-4)	
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 – 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)
Partition coefficient n-octanol/water (Log Pow)	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

quartz, conc respirable crystalline silica≥10% (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.

Stoddard solvent (8052-41-3)	
Partition coefficient n-octanol/water (Log Pow)	3.16 – 7.06

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane (17557-23-2)	
Partition coefficient n-octanol/water (Log Pow)	0.47 (QSAR, KOWWIN, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

titanium(IV) oxide	
Ecology - soil	Low potential for mobility in soil.

2-propoxyethanol (2807-30-9)	
Surface tension	71 mN/m (20 °C, 100 vol %, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Koc)	0.19 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

xylene, mixture of isomers (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
ethylbenzene (100-41-4)	
Surface tension	0.029 N/m
Partition coefficient n-octanol/water (Log Koc)	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
quartz, conc respirable crystalline silica≥10% (14808-60-7)	
Ecology - soil	No (test)data on mobility of the substance available.
Stoddard solvent (8052-41-3)	
Partition coefficient n-octanol/water (Log Koc)	2.85 – 6.74 (log Koc)
1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane (17557-23-2)	
Partition coefficient n-octanol/water (Log Koc)	1.22 (log Koc, QSAR)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with all local, regional, national and international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable. Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
- Other information : No supplementary information available.

Transportation of Dangerous Goods

- Transport document description : UN1263 PAINT (PAINT), 3, III
- UN-No. (TDG) : UN1263
- Proper Shipping Name (Transportation of Dangerous Goods) : PAINT
- TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
- Packing group : III - Minor Danger
- TDG Special Provisions : 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass),83 - Repealed SOR/2014-152
- Explosive Limit and Limited Quantity Index : 5
- Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 60

Transport by sea

- UN-No. (IMDG) : 1263
- Proper Shipping Name (IMDG) : PAINT
- Class (IMDG) : 3 - Flammable liquids
- Packing group (IMDG) : III - substances presenting low danger

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

xylene, mixture of isomers	CAS-No. 1330-20-7	0.002 – 1.5%
ethylbenzene	CAS-No. 100-41-4	0.001 – 0.5%

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

xylene, mixture of isomers (1330-20-7)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ	100 lb
ethylbenzene (100-41-4)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
CERCLA RQ	1000 lb
1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane (17557-23-2)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

15.2. International regulations

CANADA

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC
Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

No additional information available

National regulations

titanium(IV) oxide
Listed on IARC (International Agency for Research on Cancer)
ethylbenzene (100-41-4)
Listed on IARC (International Agency for Research on Cancer)
quartz, conc respirable crystalline silica\geq10% (14808-60-7)
Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

This product can expose you to ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

ethylbenzene (100-41-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	54

titanium(IV) oxide
U.S. - New Jersey - Right to Know Hazardous Substance List
2-propoxyethanol (2807-30-9)
U.S. - Pennsylvania - RTK (Right to Know) List
xylene, mixture of isomers (1330-20-7)
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
ethylbenzene (100-41-4)
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
quartz, conc respirable crystalline silica\geq10% (14808-60-7)
U.S. - New Jersey - Right to Know Hazardous Substance List

FUSION 90 SOLID COLORS (LF) LEAD FREE - GENERIC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Stoddard solvent (8052-41-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure

SDS US Endura

The information contained here has been compiled from sources considered by Endura Manufacturing Co. Ltd to be dependable and is accurate to the best of the Company's knowledge. However, neither Endura Manufacturing Co. Ltd or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

***For two component products please consult SDS of both components for proper safety and handling.*