

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Product name : EX-2C BLACK 160 NO GLOSS
Product code : CLR26303

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Endura Manufacturing Company Ltd.
12425 149 Street NW
Edmonton, T5L 2J6 - Canada
T 1-780-451-4242 - F 1-780-452-5079
info@endura.ca - www.endura.ca

1.4. Emergency telephone number

Emergency number : In the event of an emergency involving dangerous goods:
in Canada call CANUTEC at 613-996-6666 or *666 on a cellular phone.
in the US call CHEMTREC at 800-424-9300 (Account Name for US is Polyglass Coatings)

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flam. Liq. 3 H226 - Flammable liquid and vapor
Carc. 2 H351 - Suspected of causing cancer
STOT SE 3 H336 - May cause drowsiness or dizziness

Full text of H statements : see section 16

2.2. Label elements**GHS-US labeling**

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P308+P313 - If exposed or concerned: Get medical advice/attention
P312 - Call a poison center or a doctor if you feel unwell
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2) to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up

EX-2C BLACK 160 NO GLOSS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | GHS-US classification |
|-----------------|--------------------|---------|---|
| n-butyl acetate | (CAS No) 123-86-4 | 40 - 50 | Flam. Liq. 3, H226 STOT SE 3, H336 |
| carbon black | (CAS No) 1333-86-4 | < 5 | Carc. 2, H351 |
| ethylbenzene | (CAS No) 100-41-4 | 0.169 | Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 |

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off all contaminated clothing immediately.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapor.
Reactivity : Flammable liquid and vapor.

5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. NO open flames, NO sparks, and NO smoking. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

EX-2C BLACK 160 NO GLOSS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| n-butyl acetate (123-86-4) | | |
|----------------------------|-------------------------------------|---|
| ACGIH | ACGIH TWA (ppm) | 150 ppm (n-Butyl acetate; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |
| ACGIH | ACGIH STEL (ppm) | 200 ppm (n-Butyl acetate; USA; Short time value; TLV - Adopted Value) |
| ACGIH | Remark (ACGIH) | Eye & URT irr |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 710 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 150 ppm |

| ethylbenzene (100-41-4) | | |
|-------------------------|-------------------------------------|--|
| ACGIH | ACGIH TWA (ppm) | 20 ppm (Ethyl benzene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |
| ACGIH | Remark (ACGIH) | URT irr; kidney dam (nephropathy) |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |

| carbon black (1333-86-4) | | |
|--------------------------|-------------------------------------|--|
| ACGIH | ACGIH TWA (mg/m ³) | 3 mg/m ³ (Carbon black; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction) |
| ACGIH | Remark (ACGIH) | Bronchitis |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 3.5 mg/m ³ |

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Hand protection : Protective gloves.
- Eye protection : Safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Environmental exposure controls : Avoid release to the environment.

EX-2C BLACK 160 NO GLOSS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | : Liquid |
| Color | : Mixture contains one or more component(s) which have the following colour(s): Colourless Colourless to light yellow Dark grey to black White Light yellow Colourless to white Colourless or white |
| Odor | : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour(s): Fruity odour Pleasant odour Aromatic odour Petroleum-like odour Ether-like odour Mild odour Sweet odour Almost odourless Odourless Characteristic odour |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : 122 - 290 °C 251.6 - 554 °F |
| Flash point | : 26 °C 78.8 °F |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : No data available |
| Explosion limits | : 1 - 12 vol % |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Vapor pressure | : No data available |
| Relative density | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Specific gravity / density | : 1.1141 g/cm ³ |
| Solubility | : Water: Solubility in water of component(s) of the mixture : • n-butyl acetate: 0.53 g/100ml (20 °C) • xylene, mixture of isomers: < 0.02 g/100ml • Stoddard solvent: insoluble • 2-(2-methoxyethoxy)ethanol: (20 °C, Complete) • 1-methoxy-2- propanol: > 10 g/100ml (20 °C, Complete) • 2-phenoxyethanol: 2.7 g/100ml • ethylbenzene: 0.02 g/100ml • 2-methoxy-1-methylethyl acetate: 19.8 g/100ml (20 °C, soluble) • carbon black: < 0.01 g/100ml • dichlorodimethylsilane, reaction products with silica: insoluble • bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebecate: insoluble • dipropylene glycol monomethyl ether: Complete • silicon dioxide, amorphous: 0.15 g/100ml • paraffin, wax: < 0.1 g/100ml • : insoluble |
| Log Pow | : No data available |
| Auto-ignition temperature | : 407.2 °C 765 °F |
| Decomposition temperature | : No data available |
| Viscosity | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |

9.2. Other information

| | |
|--|-------------------------------|
| VOC content (Regulatory - Less water and exempt solvents) | : 482.144 g/l 4.023 lb/gal |
| VOC content (Material - Actual) | : 482.114 g/l 4.023 lb/gal |
| Percent Solids (Weight) | : 56.72 % |
| Percent Solids (Volume) | : 45.347 % |
| Percent Volatile (Weight) | : 43.274 % |
| Percent Volatile (Volume) | : 54.653 % |

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

EX-2C BLACK 160 NO GLOSS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| n-butyl acetate (123-86-4) | |
|-----------------------------------|--|
| LD50 oral rat | 10760 - 12789 mg/kg body weight (Rat; Equivalent or similar to OECD 423; Experimental value) |
| LD50 dermal rabbit | 14112 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402) |
| ATE US (oral) | 10760.000 mg/kg body weight |
| ATE US (dermal) | 14112.000 mg/kg body weight |

| ethylbenzene (100-41-4) | |
|--------------------------------|--|
| LD50 oral rat | 3500 mg/kg (Rat; Other; Experimental value) |
| LD50 dermal rabbit | 15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value) |
| LC50 inhalation rat (mg/l) | 17.8 mg/l/4h (Rat; Literature study) |
| LC50 inhalation rat (ppm) | 4000 ppm/4h (Rat; Literature study) |
| ATE US (oral) | 3500.000 mg/kg body weight |
| ATE US (dermal) | 15415.000 mg/kg body weight |
| ATE US (gases) | 4000.000 ppmV/4h |
| ATE US (vapors) | 17.800 mg/l/4h |
| ATE US (dust, mist) | 1.500 mg/l/4h |

| carbon black (1333-86-4) | |
|---------------------------------|---|
| LD50 oral rat | > 8000 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value) |
| LD50 dermal rabbit | > 3000 mg/kg (Rabbit) |

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

| ethylbenzene (100-41-4) | |
|--------------------------------|--------------------------------------|
| IARC group | 2B - Possibly Carcinogenic to Humans |

| carbon black (1333-86-4) | |
|---------------------------------|--------------------------------------|
| IARC group | 2B - Possibly Carcinogenic to Humans |

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

EX-2C BLACK 160 NO GLOSS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

| n-butyl acetate (123-86-4) | |
|-----------------------------------|--|
| LC50 fish 1 | 18 mg/l (LC50; Equivalent or similar to OECD 203; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value) |
| EC50 Daphnia 1 | 44 mg/l (EC50; Other; 48 h; Daphnia sp.; Static system; Fresh water; Experimental value) |
| Threshold limit algae 1 | 674.7 mg/l (EC50; Other; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value) |
| Threshold limit algae 2 | 200 mg/l (NOEC; Other; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value) |
| ethylbenzene (100-41-4) | |
| LC50 fish 2 | 4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value) |
| carbon black (1333-86-4) | |
| LC50 fish 1 | > 1000 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio) |
| EC50 Daphnia 1 | > 5600 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 24 h; Daphnia magna; Static system; Fresh water) |
| LC50 fish 2 | 1000 mg/l (LC0; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value) |
| Threshold limit algae 1 | > 10000 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value) |

12.2. Persistence and degradability

| n-butyl acetate (123-86-4) | |
|-----------------------------------|--|
| Persistence and degradability | Readily biodegradable in water. Low potential for adsorption in soil. Photolysis in the air. |
| ThOD | 2.21 g O ₂ /g substance |
| BOD (% of ThOD) | 0.46 |
| ethylbenzene (100-41-4) | |
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil. |
| Biochemical oxygen demand (BOD) | 1.44 g O ₂ /g substance (20d.) |
| Chemical oxygen demand (COD) | 2.1 g O ₂ /g substance |
| ThOD | 3.17 g O ₂ /g substance |
| BOD (% of ThOD) | 45.4 (20 days) |
| carbon black (1333-86-4) | |
| Persistence and degradability | Biodegradability: not applicable. Biodegradability in soil: not applicable. Adsorbs into the soil. |
| ThOD | Not applicable |

12.3. Bioaccumulative potential

| n-butyl acetate (123-86-4) | |
|-----------------------------------|--|
| BCF fish 1 | 15.3 (BCF) |
| Log Pow | 2.3 (Test data; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| ethylbenzene (100-41-4) | |
| BCF fish 1 | 1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study) |
| BCF fish 2 | 15 - 79 (BCF) |
| BCF other aquatic organisms 1 | 4.68 (BCF) |
| Log Pow | 3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |
| carbon black (1333-86-4) | |
| Bioaccumulative potential | Not bioaccumulative. |

EX-2C BLACK 160 NO GLOSS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

| n-butyl acetate (123-86-4) | |
|----------------------------|---|
| Surface tension | 0.0163 N/m (20 °C) |
| Log Koc | log Koc, SRC PCKOCWIN v2.0; 1.268/1.844; QSAR |
| ethylbenzene (100-41-4) | |
| Surface tension | 0.029 N/m |
| Log Koc | log Koc, PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value |
| carbon black (1333-86-4) | |
| Ecology - soil | Not toxic to plants. Not toxic to animals. |

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672)

T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

EX-2C BLACK 160 NO GLOSS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a
passenger vessel
Other information : No supplementary information available.

TDG

Transport document description : UN1263 PAINT (PAINT), 3, III
UN-No. (TDG) : UN1263
TDG Proper Shipping Name : PAINT
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
Packing group : III - Minor Danger
TDG Special Provisions : 59 - Substances that are listed by name in Schedule 1 must not be transported under this
shipping name. Substances transported under this shipping name may contain not more than
20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by
dry mass),83 - Repealed SOR/2014-152
Explosive Limit and Limited Quantity Index : 5
Passenger Carrying Road Vehicle or Passenger : 60
Carrying Railway Vehicle Index

Transport by sea

UN-No. (IMDG) : 1263
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : III - substances presenting low danger

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

n-butyl acetate (123-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not listed on SARA Section 313 (Specific toxic chemical listings)

CERCLA RQ : 5000 lb

ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag : T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA

CERCLA RQ : 1000 lb

carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

EX-2C BLACK 160 NO GLOSS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| ethylbenzene (100-41-4) | | | | |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | No | No | No | 54 |

| carbon black (1333-86-4) | | | | |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | No | No | No | |

| n-butyl acetate (123-86-4) | | | | |
|---|--|--|--|--|
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List | | | | |

| ethylbenzene (100-41-4) | | | | |
|---|--|--|--|--|
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List | | | | |

| carbon black (1333-86-4) | | | | |
|--|--|--|--|--|
| U.S. - New Jersey - Right to Know Hazardous Substance List | | | | |

SECTION 16: Other information

Full text of H-phrases:

| | |
|------|---|
| H225 | Highly flammable liquid and vapor |
| H226 | Flammable liquid and vapor |
| H304 | May be fatal if swallowed and enters airways |
| H332 | Harmful if inhaled |
| H336 | May cause drowsiness or dizziness |
| H351 | Suspected of causing cancer |
| H373 | May cause damage to organs through prolonged or repeated exposure |

SDS US Endura

The information contained here has been compiled from sources considered by Endura Manufacturing Co. Ltd to be dependable and is accurate to the best of the Company's knowledge. However, neither Endura Manufacturing Co. Ltd or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.