

1K Aerosol

Technical Data Sheet (TDS)

Product Description

Endura 1K Aerosol contains Endura one component coatings packaged in easy-to-use aerosol.

Product Features:

- Professional spray gun quality results
- Easy to Use
- No mess or measuring
- No equipment needed

Recommended Uses

All 1K Aerosol products are intended for industrial applications, either new build or maintenance. The 1K Aerosols are convenient for repairs or painting smaller projects.

Read the Technical Data Sheet for the specific paint being sprayed for additional information regarding the product suitability and surface preparation for the project.

Product Characteristics

The product characteristics and dry times of the products can be obtained on the product specific Technical Data Sheets.

Shelf Life:	
1K Aerosol	3 years
For unopened product (77°F (25°C))	

1K Aerosol Products Available

1K Aerosols are currently available in the following products:

- Blending Solvent
- Blender
- P-Link

Mixing

Shake the aerosol can vigorously for a minimum of 2 minutes (after the mixing ball rattles) before using.

Application

Once the product is properly shaken, perform a test spray to check the nozzle flow, substrate compatibility and color correctness. The spray fan can be adjusted for vertical or horizontal spray by turning the yellow nozzle orifice. The optimal spraying distance is 8-10 inches from the surface being painted.

To prevent the nozzle from clogging, turn the can upside down and push the spray nozzle until only propellant is being sprayed (approximately 2 seconds) between uses.

Ordering Information (sizing)

292g Aerosol	
Product code will vary depending on product	F1KXXXXX-100

Environmental Conditions

For optimum coating performance product, substrate and ambient temperature should be between 68°F-77°F (20°C-25°C). To prevent condensation during application the surface temperature must be 5°F (3°C) or more above the dew point at all times.

For use outside this range please contact your Endura Representative.

Disposal

Dispose of contents in accordance with local, state, provincial and federal regulations

Safety Precautions

Please refer to all Safety Data Sheets (SDS) before using this product. SDS sheets can be found on our website at www.endurapaint.com.